Department of Information Technology & Communication (DoIT & C) ACP Exam: 2014 Paper: II

1 0	f 100
100	RPSC_March-2016_Paper 2
The	correct order of steps for a system development life cycle is
0	Analysis, Planning, design, test, document, implement, evaluate.
0	Planning, Analysis, implement, design, document, test, evaluate.
0	Planning, Analysis, design, document, implement, test, evaluate.
0	Analysis, Planning, design, implement, evaluate, test, document.
2 0	f 100
101	RPSC_March-2016_Paper 2
	nslating a required task for system development into a series of commands that a computer will be to understand is
0	Project design
0	Installation
0	Programming
0	Systems analysis
3 o	f 100
102	RPSC_March-2016_Paper 2
Des	signers create system prototypes to
0	make the programmers understand how the system will function.
0	make the user visualize how the system will look like when it is developed and receive feedback

give a demo of the system to his administrating system manager to show as report
make both programmers and user understands how the system will look and function
4 of 100
103 RPSC_March-2016_Paper 2
Dotted arrows in a DFD are used to represent
Data flow
Control flow
Result
Simple connector
5 of 100
104 RPSC_March-2016_Paper 2
A data dictionary has consolidated list of data required for i. Documenting
ii. Input form designing
iii. Temporarily stored items
(i) and (ii)
(i),(ii) and (iii)
(i) and (iii)
None of the these
6 of 100
105 RPSC_March-2016_Paper 2
Hierarchy of maintenance requests is in order

i. maintenance controller

ii. system supervisor iii. change control authority
ii to i to iii
i to ii to iii
iii to i to ii
III to I to II
maintenance is not possible in this way
7 of 100
106 RPSC_March-2016_Paper 2
The data which is eligible for record keeping during maintenance
source statements added by the program change
number of machine code instructions
number of processing failures associated with the runs
All of these
8 of 100
107 RPSC_March-2016_Paper 2
In the model of total effort expended in maintenance $M = a + K(b-c)$, a represents
an empirical constant
productive effort
complexity attributed to the lack of good design and documentation
measure of the familiarity with the software

Debugging is

- creating program code.
- creating the bugs in the program for testing
- finding and correcting errors in the program code.
- creating the algorithm.

10 of 100

109 RPSC_March-2016_Paper 2

Match the following

1. Verification	K. checking whether the software meets the decided specification
2. Validation	L. converting logics into computer program
3. Testing	M. checking whether the software meets customer requirements
4. Coding	N. to check is the software is giving desired output for all inputs

1-N, 2-L, 3-M, 4-N

1-M, 2-K, 3-N, 4-L

1-K, 2-N, 3-M, 4-L

1-K, 2-M, 3-N, 4-L

11 of 100

110 RPSC_March-2016_Paper 2

Which is not valid difference between verification and validation

Verification	Validation
Verification is carried out before the	Validation activity is carried out just
Validation.	after the Verification.

Verification	Validation
Testing like black box testing,	Reviews, Meetings and Inspections
white box testing and gray	are done under this.
box testing are done under	
this.	

Verification	Validation
Cost of errors caught in	Cost of errors caught in Validation is
Verification is less than errors found	more than errors found in
in Validation.	Verification

Verification	Validation
Execution of code is not comes	Execution of code is comes
under Verification.	under Validation.

111 RPSC_March-2016_Paper 2

Which statement is correct about of testing

It is done only for customer satisfaction that the product is working properly and is optional step.

It is a problem statement which lists specific inputs that are typically expected to be entered by the user and precise output values that a perfect program would return for those input values

It is finalized when the coding is completed

All of these

13 of 100

112 RPSC_March-2016_Paper 2

The primary objective of system implementation is i. to build a system prototype

ii. to train users to operate the system iii. to implement designed system using computers iv. write programs, create databases and test with live data
C i, iii
i, ii, iii
° ii ,iii
iii, iv
14 of 100
113 RPSC_March-2016_Paper 2
Which design is perfect for long use, maintainability and up-gradation
use good software tools
use the best hardware available
design the system in independent modules
Create versions of the program frequently
15 of 100
114 RPSC_March-2016_Paper 2
The system analyst is required to perform the task(s) include i. defining and prioritizing information requirement of an organization ii. gathering data, facts and opinions of users in an organization iii. drawing up specifications of the system for an organization iv. designing, coding and evaluating the system
i and ii
i, ii and iv
i, ii and iii

i, ii, iii and iv
16 of 100
115 RPSC_March-2016_Paper 2
Which of the following is not the primary design objective
Cost
Reusability
Understandable code for user
Security
17 of 100
116 RPSC_March-2016_Paper 2
A system when made of several discrete components is called
Top-down
Bottom up
Modular
Linear
18 of 100
117 RPSC_March-2016_Paper 2
Which of the following is true for cohesion and coupling
Coupling taken place between multiple modules whereas cohesion is the strength of various elements inside a module
A good design must have very high cohesion

A good design must have very low coupling
C All of these
19 of 100
118 RPSC_March-2016_Paper 2
Which of the following is not advantage of structured design
Critical interfaces are designed first
Controls for upgrades are very easy and low cost
Early versions of design can give pre-review of system
Real life systems can be easily modeled
20 of 100
119 RPSC_March-2016_Paper 2
In IPO charts P stands for
Program
Process
Publish
Presumption
21 of 100
120 RPSC_March-2016_Paper 2
Which is not a reason to consult user while designing of structured walk
Probability of success improves with involvement of user

Feedback is received which is very important
User and programmer can communicate to decide the price of the software
User can be trained and made understood about system
22 of 100
22 01 100
121 RPSC_March-2016_Paper 2
The correct order of input form design stages is
i. Determining the contents of the input
ii. Choosing appropriate input device
iii. Identify the inputs required by the system iv. Designing forms for input
W. Doolgimig forme for input
C iii-i-ii-iv
C i-iii-ii-iv
1 III II IV
i-iii-iv-ii
iii-i-iv-ii
23 of 100
122 RPSC_March-2016_Paper 2
From the following which is not the activity of software maintenance
The following which is not the dearny of contrare maintenance
corrective maintenance
adaptive maintenance: modifies software to properly interface with a changing environment
adaptive maintenance, modines software to properly interface with a changing environment
preventive maintenance
reverse engineering
TOVOTOC Chighlicoling
24 of 100

123 RPSC_March-2016_Paper 2		
Correct order of stages of testing		
Unit, integration, system, regression, acceptance		
System, regression, unit, integration, acceptance		
Unit, system, regression, integration, acceptance		
System, integration, unit, acceptance, regression		
25 of 100		
124 RPSC_March-2016_Paper 2		
Organizational chart is an example of		
° IPO		
° HIPO		
Step chart		
Process chart		
26 of 100		
125 RPSC_March-2016_Paper 2		
Structured charts are developed after		
Designing		
Coding		
C Requirement gathering		
C Requirement analysis		

27	27 of 100		
126	126 RPSC_March-2016_Paper 2		
Out	of following which comes under requirement specification		
0	Functional implementation		
0	Temporary Data collection		
0	User feedback about project		
0	Data flow models		
28	of 100		
127	RPSC_March-2016_Paper 2		
repr	model in which system development is broken down into a number of sequential sections or stages resented by boxes, with each stage being completed before work starts on the following one. The buts from one stage are used as inputs to the next.		
0	Spiral model		
0	Waterfall model		
0	Structured model		
0	None of these		
29	of 100		
128	RPSC_March-2016_Paper 2		
The	spiral model is advantageous than waterfall model		
0	When the requirements of the system are well understood by the users		
0	When the requirements are not well formed or understood by the users		
0	When the product comes after one stage easily		

When all the functional requirements are available after requirement analysis

30 of 100

129 RPSC_March-2016_Paper 2

Match the following

Backtracking Approach	 a) Black box testing technique
2. Software Maturity index	b) White box testing technique
3. Equivalence Partitioning Testing	c) Debugging Technique
4. Control Structure Testing	d) Maintenance Metric

1-c, 2-d, 3-a,4-b

1-d, 2-c, 3-b,4-a

1-b, 2-a, 3-c,4-d

1-a, 2-b, 3-d,4-c

31 of 100

130 RPSC_March-2016_Paper 2

Cost-Benefit Analysis is performed during

Analysis phase

C Design phase

Feasibility study phase

Implementation phase

32 of 100

131 RPSC_March-2016_Paper 2

Project risk factor is considered in

0	Spiral model
0	Waterfall model
0	Prototyping model
0	Iterative enhancement model
33	of 100
132	RPSC_March-2016_Paper 2
abs	oftware project classifies system entities, their activities and relationships. The classification and traction of system entities is importantmethodology most clearly shows the classification abstraction of entities in the system
0	Prototyping Model
0	Data Flow Model
0	RAD model
0	None of these
34	of 100
133	RPSC_March-2016_Paper 2
In u	nit testing, interface testing is performed to assess
0	Efficiency
0	Behavior
0	Functional Independence
0	Internal logic of code
35	of 100

134 RPSC	_March-2016_	Paper	2
-----------------	--------------	-------	---

Which of following is NOT defined in a good software requirement specification (SRS) document

- Functional requirement
- Non Functional requirement
- Goals of Implementation
- Algorithms for software Implementation

36 of 100

135 RPSC_March-2016_Paper 2

Match the following based on Design

i.	Import Coupling	a. Nominal communication between modules
ii.	Procedural call Coupling	b. Minimum communication between modules
iii.	External Coupling	c. Declaration of a module in another module
iv.	Low Coupling	d. Communication between internal modules & Collaborators

i-c, ii-d, iii-a, iv-b

i-d, ii-c, iii-b, iv-a

i-a, ii-c, iii-d, iv-b

i-c, ii-a, iii-d, iv-b

37 of 100

136 RPSC_March-2016_Paper 2

Which of the following is not regression test case?

0	A representative sample of tests that will exercise all software functions
0	Additional tests that focus on software functions that are likely to be affected by the change
0	Tests that focus on the software components that have been changed
0	Low-level components are combined into clusters that perform a specific software sub-function
38	of 100
137	RPSC_March-2016_Paper 2
Afte	r Development phase, a document is prepared
0	Program specification
0	System specification
0	Design specification
0	None of these
39	of 100
138	RPSC_March-2016_Paper 2
A di	agram that shows the major subsystems in an object-oriented system is called a
0	System flowchart
0	Design class diagram
0	Class diagram
0	Component diagrams
40	of 400
40	of 100
139	RPSC_March-2016_Paper 2

During the planning phase of the system development life cycle (SDLC), the helps to define the scope of the problem.
critical path method (CPM) chart
project evaluation and review technique (PERT) chart
proof of concept prototype
Context diagram
41 of 100
140 RPSC_March-2016_Paper 2
Clients play what role in the development of a new system?
Develop the project plan
Define the business processes
Fund the project
Lead the project team
42 of 100
141 RPSC_March-2016_Paper 2
Questionnaires can be useful in information gathering when users
are widely distributed geographically
need prompting to respond to questions
are not well-informed
do not have time for interviews

142 RPSC_March-2016_Paper 2
requirements are based on the procedures and rules that the organization uses to run its business.
Functional
Logical
Physical
None of these
44 of 100
143 RPSC_March-2016_Paper 2
The first item to be reviewed during a structured walkthrough is the documentation that was developed as part of the phase of the systems development life cycle (SDLC).
design
analysis
planning
implementation
45 of 100
144 RPSC_March-2016_Paper 2
Error report is an example of
Process
Output process
C Input process
None of these

46 of 100 145 RPSC_March-2016_Paper 2 An external entity in the system is Unit outside the system and controllable by system analyst External unit which will be designed A unit which is not shown in DFD A unit outside the system and works completely independent manner 47 of 100 146 RPSC_March-2016_Paper 2 The controlling factor which does not governs the software maintainability use of standardized programming languages inefficient maintenance team taking much time standardized structure of the documentation availability of test cases 48 of 100 147 RPSC_March-2016_Paper 2 The code used for the validation purpose is known Debugging code Self-checking code Sequence code Group classification code

49	49 of 100	
148	RPSC_March-2016_Paper 2	
Fea	sibility checking is the step performed	
0	Before requirements specifications are drawn up	
0	during the period when requirements specifications are drawn up	
0	After all requirements specifications are drawn up	
0	at any time	
50	of 100	
149	RPSC_March-2016_Paper 2	
Wh	at is incorrect about DFDs	
0	process models have as many level 1 diagrams as there are processes on the level 0 diagram	
0	every process in the level 1 DFD would be decomposed into its own level 1 DFD	
C they	The purpose of the level 0 DFD is to show all the major high-level processes of the system and how are interrelated	
0	level 1 DFD shows how level 0 processes operates in greater detail	
51	of 100	
	RPSC_March-2016_Paper 2	
	ective software project management focuses on four P's which are	
0	people, performance, payoff, product	
0	people, product, performance, process	
0	people, product, process, project	

0	people, process, payoff, product
52	of 100
151	RPSC_March-2016_Paper 2
The	e first step in project planning is to
0	determine the budget
0	select a team organizational model.
0	determine the project constraints.
0	establish the objectives and scope
53	of 100
152	RPSC_March-2016_Paper 2
	e application of knowledge, skills, tools and techniques to project activities to meet the project uirements.
0	Software quality control
0	Software project management
0	Software process management
0	Software project planning
54	of 100
153	B RPSC_March-2016_Paper 2
Wh	ich of the following is a tool of time management for software development
0	Project network diagrams
0	Gantt charts

Critical-path analyses

All of these

55 of 100

154 RPSC_March-2016_Paper 2

Match the project manager responsibilities with their tasks

Responsibilities	Tasks
i. interpersonal responsibilities	a. disseminating information about tasks to the project team
ii. informational responsibilities	b. allocating resources according to the project plan
iii. decisional responsibilities	c. leading the project team

- i-c, ii-a, iii-b
- i-a, ii-c, iii-b
- i-a, ii-b, iii-c
- i-c, ii-b, iii-a

56 of 100

155 RPSC_March-2016_Paper 2

What information is not essentially required in a project progress report

- Reporting period to which it refers
- Days taken and cost to complete the report
- Authors of the report
- Date of submission

57 OT 100		
156 RPSC_March-2016_Paper 2		
Which of following is not the aim of project progress report		
Provide an overview of project's progress up to date		
To keep it as a document for customer satisfaction		
Ensure that the key stakeholders are regularly informed		
Inform the key stakeholders about issues that require immediate action or resolution		
58 of 100		
157 RPSC_March-2016_Paper 2		
Objectives of risk management do not include		
Minimize the effort in software coding		
Minimize adverse impacts to project scope, cost, and schedule		
Maximize opportunities to improve the project's objectives with lower cost, shorter schedules, enhanced scope and higher quality		
Minimize management by crisis		
59 of 100		

Match the processes with their deliverables

Processes			Deliverables	
i.	Risk management planning	a.	Prioritized list of risks classified as high, moderate, or low	
ii.	Risk identification	Ъ.	RMP document	
iii.	Qualitative risk analysis	C.	Risk register	
iv.	Quantitative risk analysis	d.	Numerical analysis of the project'slikelihood of achieving its overallobjectives	

0	i-b, ii-c, iii-a, iv-d
0	i-c, ii-a, iii-d, iv-b
0	i-b, ii-c, iii-d, iv-a

i-c, ii-d, iii-a, iv-b

60 of 100

159 RPSC_March-2016_Paper 2

Which of the following is not an information gathering technique for risk identification?

Brain Storming
Risk Calculator

SWOT Analysis

Interviewing

61 of 100

160 RPSC_March-2016_Paper 2

Which is not a suitable difference in qualitative and quantitative risk analysis?

Qualitative analysis assesses the likelihood and impact of identified risks to determine whereas quantitative analysis is a way of numerically estimating the probability that a project will meet its cost and time objectives.

Quantitative risk analysis involves statistical techniques whereas qualitative analysis is found using impact matrix.
Qualitative risk analysis generally follows qualitative analysis.
None of these
62 of 100
161 RPSC_March-2016_Paper 2
Which statement is false?
Organizations that achieve high levels of maturity in the people management area have a higher likelihood of implementing effective software engineering practices.
The software developer and analyst must meet to define product objectives and scope alone.
Without information of technical and management constraints, it is impossible to define accurate estimates of the cost and risk.
Umbrella activities are independent of any one framework activity and occur throughout the process
63 of 100
162 RPSC_March-2016_Paper 2
Which is not the meaning of W's W ⁵ HH
Which is not the meaning of W.S. W. Till
Why is the system being developed?
Who is responsible for a function?
What will be done, by when?
Where the organizational hierarchy plays its role?
64 of 100

Defect removal efficiency (DRE) can be computed as (where E represent effort and D represent defects)		
DRE = Echange / (Echange + Dchange		
DRE = Dchange / (Echange - Dchange)		
C DRE = Echange / (Echange - Dchange)		
C DRE = Dchange / (Echange + Dchange)		
65 of 100		
164 RPSC_March-2016_Paper 2		
Which is not a quality metric?		
© Maintainability		
C Integrity		
Usability		
Controllability		
66 of 100		
165 RPSC_March-2016_Paper 2		
Which of the following condition if hold true suggests that process is out of control?		
A single metrics value lies outside the upper natural process limit (UNPL)		
$^{\hbox{\scriptsize C}}$ Two out of three successive metrics values lie more than two standard deviations away from average metric value $A_{\mbox{\scriptsize m}}$		
All the metrics cannot be calculated together		
Eight consecutive metrics values lie on one side of A _m		

166 RPSC_March-2016_Paper 2		
Which is not a reusable software resource from the following		
Off-the-shelf components		
Full-experience components		
Environmental components		
Partial-experience components		
68 of 100		
167 RPSC_March-2016_Paper 2		
Which of the following is not a good and reliable cost and effort estimate		
Delay estimation until late in the project		
Ask from customer about his budget		
Base estimates on similar projects that have already been completed		
Use relatively simple decomposition techniques to generate project cost and effort estimates		
69 of 100		
168 RPSC_March-2016_Paper 2		
In a sample of empirical estimation model M represents $E = A + B \ x \ (M)^C$		
Effort		
Estimation variable		

C Time

Empirical constant

169 RPSC_March-2016_Paper 2

COnstructive COst Model (COCOMO) model addresses

- Application composition model
- Early design stage model
- Maintenance model
- Post-architecture-stage model

71 of 100

170 RPSC_March-2016_Paper 2

In the following effort estimation model, B represents

$$E = [LOC \times B^{0.333}/K]^3 \times (1/t^4)$$

- Effort
- Project duration
- Special skills factor
- Productivity parameter

72 of 100

171 RPSC March-2016 Paper 2

Not a basic function of automated estimation

- Selecting project activities
- Predicting software effort
- Predicting software cost

Maintenance plan creation		
73 of 100		
172 RPSC_March-2016_Paper 2		
Which of the following is not a general risk component		
Performance risk		
Cost risk		
Support risk		
Payment Risk		
74 of 100		
74 01 100		
173 RPSC_March-2016_Paper 2		
Which of the following is not a common step to mitigate the risk		
Train project teams so that they do not take risk		
Meet with current staff to determine causes for turnover		
Mitigate those causes that are under our control before the project starts		
Once the project commences, assume turnover will occur and develop techniques to ensure continuity when people leave		
75 of 100		
174 RPSC_March-2016_Paper 2		
Which of the following is not generally a reason for late project delivery		
An unrealistic deadline established by someone outside the software development group and forced on managers and practitioner's within the group		

Changing customer requirements that are not reflected in schedule changes
Customer not releasing payment
An honest underestimate of the amount of effort and/or the number ofresources that will be required to do the job
76 of 100
175 RPSC_March-2016_Paper 2
is an activity that distributes estimated effort across the planned project duration by allocating the effort to specific software engineering tasks
Software project scheduling
Software project management
Software planning
Software effort estimation
77 of 100
176 RPSC_March-2016_Paper 2
Issues guiding software project scheduling
Interdependency
Time allocation
Both Interdependency & Time Allocation
Both interdependency & Time Allocation
None of these

Reliable decomposition technique under software project estimation is		
Process based estimation		
Software sizing		
Problem based estimation		
C All of these		
79 of 100		
178 RPSC_March-2016_Paper 2		
The correct order of earned value calculation steps is i. Estimate effort for work planned ii. budgeted cost of work scheduled iii. Estimate budget for work performed		
C i-ii-iii		
C II-I-III		
C III-I-II		
C ii-iii-i		
80 of 100		
179 RPSC_March-2016_Paper 2		
The auditing and reporting functions of management are part of		
Cost of quality		
C Quality control		
Quality assurance		
C Quality evaluation		

81	81 of 100		
180 RPSC_March-2016_Paper 2			
Which of the following is not a fundamental source of change			
0	New business or market conditions dictate changes in product requirements		
0	New customer needs demand modification		
0	Problems in the organization		
0	Commitment to other customer		
82	of 100		
101	RPSC_March-2016_Paper 2		
obje	combines procedures and tools to manage different up-gradations of configuration ects that are created during the software process		
0	Maintenance schedule		
0	Version control		
0	Evolutionary design		
0	Data flow model		
83	of 100		
182	RPSC_March-2016_Paper 2		
Wh	ich of the following risk is the failure of a purchased component to perform as expected?		
0	Product risk		
0	Project risk		
0	Business risk		
0	Programming risk		


84	of 100				
183	183 RPSC_March-2016_Paper 2				
Sof	Software interoperability is:				
0	The ability of a software system to work on different hardware platforms				
0	The ability of a software system to work under different operating systems				
© exc	The ability of a software system to exchange information with other software systems and to use the hanged information				
0	The ability to replace a software system with another software system that has similar functionality				
85	of 100				
184	RPSC_March-2016_Paper 2				
Сус	clomatic Complexity is :				
0	number of operands in program				
0	number of decision points +1				
0	number of operators in program				
0	None of these				
86	of 100				
185	RPSC_March-2016_Paper 2				
Gra	de of a product				
0	Means the same thing as quality				
0	can be used interchangeably with quality				
0	Is the level of product or service				

None of these

87 of 100

186 RPSC_March-2016_Paper 2

The following diagram shows that:



- Specification is completed before delivery
- Specification is not completed until delivery
- Specification is part of delivery
- Specification is an ongoing activity

88 of 100

187 RPSC_March-2016_Paper 2

The allows determination of early start, early finish, late start and late finish

- Three point estimates
- Flow chart technique
- Precedence diagramming method
- Critical Path method

89 of 100

188 RPSC_March-2016_Paper 2		
	is the degree to which the design specifications are followed during manufacturing	
0	Quality of development	
0	Quality of conformance	
0	Quality of design	
0	None of the these	
90	of 100	
189	RPSC_March-2016_Paper 2	
Top-level problem solving and internal team coordination are managed by a team leader in which approach		
0	Controlled centralized	
0	Controlled decentralized	
0	Democratic decentralized	
0	Partial centralized	
91 (of 100	

Associate Potential Risk Conditions Associated With Each Knowledge Area

Knowledge Area		Risk Conditions		
i.	Integration	a. Poor resource allocation		
ii.	Scope	b. Poor definition of scope		
iii.	Time	c. Early release of competitive products		
iv.	Cost	d. Inadequate productivity		

i-a, ii-b, iii-c, iv-d

i-b, ii-a, iii-d, iv-c
i-d, ii-b, iii-a, iv-c
i-b, ii-c, iii-a, iv-d
92 of 100
191 RPSC_March-2016_Paper 2
Which of the following term is best defined by the statement: "The underlying technology on which the system is built is superseded by new technology."?
Product competition
Technology change
Requirements change
None of the mentioned
93 of 100
192 RPSC_March-2016_Paper 2
Which is a project attribute?
Resources
Efforts
User feedback
Hardware up-gradation
94 of 100

Which is not an umbrella activity under software Engineering?

0	Software quality assurance
0	Software configuration management
0	Document preparation and production
0	Software Encryption
95	of 100
194	RPSC_March-2016_Paper 2
Pro	duct quality is defined as:
0	Delivering a product with correct requirements
0	Delivering a product using correct development procedures
0	Delivering a product which is developed iteratively
0	Delivering a product using high quality procedures
96	of 100
	RPSC_March-2016_Paper 2
	ich type of risk factor is most likely to cause problems for a software project which develops military ware?
0	Unused or unusable software
0	Legal expenses
0	Excessive paperwork
0	High maintenance costs
07	of 100
4/	

is a technique used to show the effects of change of one or more variables on
an outcome.
Statistical Analysis
Sensitivity Analysis
Proportional Analysis
Quantitative Analysis
98 of 100
197 RPSC_March-2016_Paper 2
A is developed using historical cost information that relates some software metric to the project cost
Algorithmic cost modeling
Expert judgment
Estimation by analogy
Parkinson's Law
00 05 400
99 of 100
198 RPSC_March-2016_Paper 2
Halstead's source code metrics are based on the number of
modules in the program
operands in the program
operators in the program
Both operator and operands in the program

4	n	n	of	4	n	n
	U	U	UI		U	U

Which of the following is not an approach to software cost estimation?

- Empirical
- Heuristic
- Analytical
- Critical

ANALYST-C		MMER (DOIT		14 PAPER			
		n Date 17-03-					
		sue Date-18-1					
	Answer key as per the Question Paper uploaded on Website						
Qno	RES		Qno	RES			
1	3		51	3			
2	3		52	4			
3	4		53	2			
4	2		54	2			
5	2		55	1			
6	*		56	2			
7	4		57	2			
8	2		58	1			
9	3		59	1			
10	4		60	2			
11	2]	61	4			
12	2]	62	2			
13	4]	63	4			
14	3		64	1			
15	3		65	4			
16	3		66	*			
17	3		67	3			
18	4]	68	2			
19	4	1	69	2			
20	2	1	70	*			
21	3	1	71	3			
22	1	1	72	4			
23	4	1	73	4			
24	1	1	74	1			
25	2	1	75	3			
26	1	1	76	1			
27	4	1	77	3			
28	2		78	4			
29	2		79	2			
30	1	1	80	3			
31	3	1	81	4			
32	1	1	82	2			
33	4	1	83	1			
34	3	1	84	3			
35	4	1	85	2			
36	4	1	86	3			
37	4		87	4			
38	2	1	88	4			
39	*	1	89	2			
40	4	1	90	1			
		-					
41	3		91	1			
42	1		92	2			
43	1		93	1			
44	2		94	4			
45	2		95	1			
46	2		96	*			
47	2		97	2			
48	2		98	1			
49	1		99	4			
50	2		100	4			

^{*} Means deleted